

Features:

- Compressed air free;
- Versatile and simple operation;
- High-visibility color touch screen interface;
- Automatic command of cycles;
- F0 control of sterilization cycle;
- Validated cycles for hospital or laboratory loads;
- Count of the number of sterilization cycle performed;
- Digital printer;
- Real-time printing of cycle parameters;
- Safety-stop system for door movement in case of obstruction;
- Safety system against door opening in mid-cycle in case of power failure;
- Incorporated energy and water saving systems;
- Extensive list of errors associated with eventual cycle-specific failures;
- Equipment fully built in stainless steel, with chamber and doors in AISI 316L;
- Optionally supplied with 1 or 2 electric operated sliding doors;
- Control valves electric operated;
- Vacuum system with liquid ring vacuum pump;
- Accurate PT-100 temperature sensors and electronic absolute pressure sensors;
- Integral steam jacket;
- Audible alarms.



Accessories:

- Charging system • Water softener • Reverse osmosis system • Graphic record device • Product probe • Analog manometers • Cabinet pannels • Stainless steel valves and tri-clamp connections • Pneumatic valves • Dual system steam supply • Built-in steam generator with independent water inlet. • Steam generator automatic flush drainage system
- Software for documentation and traceability.



- Option 1:**
- One level loading car
 - Transfer carriage



- Option 2:**
- Two level loading car
(removable intermediate level)
 - Transfer carriage



- Option 3:**
- Removable intermediate shelf
 - Bottom shelf

Available Models	Chamber volume (l)	Chamber dimensions (cm) (width x height x depth)	Overall size (cm) (width x height x depth)
AJC 404066 -1D/2D	105	40 x 40 x 66	70 x 183 x 98
AJC 505066 -1D/2D	165	50 x 50 x 66	80 x 183 x 98
AJC 5050100 -1D/2D	250	50 x 50 x 100	80 x 183 x 132

Other capacity upon request.